

Work Zone Safety and Aerial Trucks

For Sale, Rent, Repair, Maintenance, and Custom-Built Trucks to Your Specifications.

Elliot L60R

Bucket Truck



WORKING HEIGHT: 63' / 19,2 m
WORKING SIDE REACH: 56' / 17,1 m
BOOM SECTIONS: 3 platform type EZR removable
PLATFORM CAPACITY: 500 lb / 227kg
PLATFORM SIZE: 40"X60" / 102X152 cm
JIB WINCH CAPACITY: 500 lb / 227 kg 793 kg
MAIN WINCH CAPACITY: 5,900 lb / 2676 kg

OUTRIGGER TYPE FRONT: A-type
OUTRIGGER TYPE REAR: Out-down
OUTRIGGER SPREAD REAR: 18' / 5,5 m
UNIT WEIGHT (BARE): 13,500 lb / 6123 kg
OVERALL HEIGHT: 12'0" / 3,6 m
RECOMMENDED CAB TO AXLE (CA): 120" / 305 cm
RECOMMENDED GVWR: 25,999 lb / 11

Versalift VST-40

Bucket Truck



GENERAL SPECIFICATIONS
Horizontal Reach: 30'-2" (9.2 m)
Maximum Platform: Capacity 600 lbs.
Platform Rotation: 180°

BOOM ACTION
Outer/Inner Boom Articulation: -25' to +85'
Inner Boom Extension: 79" (2.0 m)
Lower Boom Articulation: 0° to +87°
Rotation: 360° Continuous

HEIGHT WITH STANDARD PEDESTAL
Bottom of Platform Height: 36'-4"
Working Height: 41'-4" (12.6 m)
Stowed Travel Height: 10'-6" (3.2 m)

INSULATION (WHERE APPLICABLE)
Upper Boom Insulation Gap: 46" (1.2 m)
Lower Boom Insulation Gap: 12" (305 mm)

VEHICLE REQUIREMENTS
Cab to Axle (minimum): 84" (2.14 m)
GVWR: 17,500 lbs. (7,940 kg)

Versalift SST-40

Bucket Truck



GENERAL SPECIFICATIONS
Horizontal Reach: 27 ft. 9 in. (8.5 m)
Standard Platform Capacity: 300lbs. Maximum
Platform Capacity: 450 lbs.
Outer Boom Lift Eye Capacity: 500 lbs.

WITH STANDARD PEDESTAL
Height to Bottom of Platform: 40 ft. 0 in.
Working Height: 45 ft. 0 in.
Stowed Travel Height: 10ft. 4 in.
Weight of Lift: 2335 lbs.

HYDRAULIC SYSTEM
Flow Rate: 3 GPM (11 lpm) on ENH/EIH;
2 GPM (81 lpm) on NE
Filtration: 10 micron return; 100 mesh suction
System Type: Open Center

BOOM ACTION
Inner Boom: 116 in (2.9 m) Extension
Outer Boom: -14° to 74°
Lower Boom: -7° to vertical
Rotation: 370° non-continuous

INSULATION GAP
Upper Boom fully retracted Flow: 42 in. Lower
Boom Insert (optional): 12 in. (0.3 m)

providing quality products and service while developing our reputation of excellence

Attenuator Trucks



- No CDL required
- Automatic transmissions
- 14'6" body
- **All controls from inside the cab**
- 62.5 MPH rated MASH Attenuator
- NJ DOT Certified
- **Daily/Weekly/ Monthly Rentals**

Cone Trucks



- 20' Steel Flatbed with Bulkhead and center mounted vision screen.
- **42" High railings**
- Full length E-Track on both sides of body
- 6" Kick plate on both sides of body
- **50" wide gate on Curb side**
- All steel to be painted safety yellow.
- **Rear Sign Holders installed on body.**
- Retractable curb side Ladder
- Man-basket painted safety yellow with side safety doors.
- **2" Combo hitch with flat 4 trailer plug**
- 2 Rear flashing Yellow LED lights on basket
- 4 Flashing yellow LED lights on truck.
- **8 LED work lights**
- 2 Grille mounted LED strobe lights
- Rear mounted CCTV safety camera system.

BSL 20-70 Scissor Truck



- 20' high by 8' feet wide
- The **platform extends 3 feet** on either side hydraulically allowing a **14' wide working platform**
- 42" high side rails
- **7,000 lbs.** platform capacity
- 4 LED spotlights
- Front, rear, and side strobe lights
- **26,000lbs - 33,000lbs GVW** (Non-CDL & CDL options available)
- Automatic transmission
- High rail option available

BSL 16-30 Scissor Truck



- 20' high by 8' feet wide
- **42" high side rails**
- **3,000 lb.** capacity
- Front and rear strobe lights
- **14,500-19,500 GVW (No CDL required)**
- Automatic transmission
- **Curb side controls**
- 4 LED Spotlights